





PIÑONES PARA TAPER TEMPLADOS - DIN 8187 - ISO 606

SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH

3/8" x 7/32"

9,525 x 5,72 mm
Rodillo 6,35 mm
06B - 1



B1	C	r3
5,3	1	10




Material C 43 UNI 7847

Z	de	dp	dm	simple		Kg.
				A	taper	
17	55,5	51,83	45	22	1008	0,11
19	61,6	57,86	45	22	1008	0,15
21	67,6	63,90	46	22	1008	0,18
23	73,7	69,95	63	25	1210	0,27
25	79,7	75,99	63	25	1210	0,32

Z	de	dp	dm	simple		Kg.
				A	taper	
27	85,7	82,04	63	25	1210	0,34
30	94,8	91,12	63	25	1210	0,39

1/2" x 5/16"

12,7 x 7,75 mm
Rodillo 8,51 mm
08B - 1



B1	C	r3
7,2	1,3	13



Material C 43 UNI 7847

Z	de	dp	dm	simple		Kg.
				A	taper	
15	66,5	61,80	45	22	1008	0,16
17	74,5	69,11	60	25	1210	0,22
19	82,5	77,15	63	25	1210	0,33
21	90,6	85,21	71	25	1610	0,36
23	98,7	93,26	76	25	1610	0,50

Z	de	dp	dm	simple		Kg.
				A	taper	
25	106,7	101,32	76	25	1610	0,56
27	114,8	109,39	76	25	1610	0,63
30	126,9	121,49	90	32	2012	0,91

5/8" x 3/8"

15,875 x 9,65 mm
Rodillo 10,16 mm
10B - 1



B1	C	r3
9,1	1,6	16

Material C 43 UNI 7847

Z	de	dp	dm	simple		Kg.
				A	taper	
13	73,2	66,33	47	22	1008	0,23
15	83,2	76,35	60	25	1210	0,30
17	93,3	86,39	71	25	1610	0,38
19	103,3	96,44	75	25	1610	0,54
21	113,4	106,51	76	25	1610	0,65

Z	de	dp	dm	simple		Kg.
				A	taper	
23	123,5	116,58	76	25	1610	0,77
25	133,6	126,66	90	32	2012	1,05
27	143,6	136,74	90	32	2012	1,17
30	158,8	151,87	90	32	2012	1,40



PIÑONES PARA TAPER TEMPLADOS- DIN 8187 - ISO 606




SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH

3/4" x 7/16"

19,05 x 11,68 mm
Rodillo 12,07 mm
12B - 1

B1	C	r3
11,1	2	19

Material : C 43 UNI 7847



Z	de	dp	dm	simple		
				A	taper	Kg.
13	87,8	79,60	60	25	1210	0,35
15	99,8	91,62	70	25	1610	0,44
17	111,9	103,67	76	25	1610	0,66
19	123,9	115,73	90	32	2012	0,94
21	136,0	127,81	102	44	2517	1,24



Z	de	dp	dm	simple		
				A	taper	Kg.
23	148,1	139,90	108	44	2517	1,70
25	160,2	151,99	108	44	2517	1,93
27	172,3	164,09	108	44	2517	2,14
30	190,4	182,24	108	44	2517	2,60

1" x 17,02 mm

25,4 x 17,02 mm
Rodillo 15,88 mm
16B - 1

B1	C	r3
16,2	2,5	26

Material : C 43 UNI 7847



Z	de	dp	dm	simple		
				A	taper	Kg.
15	133,7	122,16	76	38	1615	1,30
17	149,8	138,23	90	32	2012	1,59
19	165,9	154,31	108	44	2517	2,29
21	182,0	170,42	110	44	2517	2,81
23	198,1	186,53	110	44	2517	3,38



Z	de	dp	dm	simple		
				A	taper	Kg.
25	214,2	202,66	110	44	2517	3,97
27	230,4	218,79	110	44	2517	4,55
30	254,6	242,99	120	44	2517	5,97

1"1/4 x 3/4"

31,75 x 19,56 mm
Rodillo 19,05 mm
20B - 1

B1	C	r3
18,5	3,5	32

Material : C 43 UNI 7847



Z	de	dp	dm	simple		
				A	taper	Kg.
15	167,7	152,72	110	44	2517	3,39
17	187,7	172,78	110	44	2517	5,07
19	207,9	192,91	110	44	2517	6,75
21	228,0	213,04	120	44	2517	7,70
23	248,2	233,17	120	44	2517	8,78

Z	de	dp	dm	simple		
				A	taper	Kg.
25	268,4	253,33	120	44	2517	9,50